



FITTING HOLES(SCALE 3:1)

MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		Q60LP			
MATERIAL		HOUSING-ABS			
		LENS-PC			
		BRACKET-PC			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.		60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.08W	MAX. 0.140A
			AC110V ~ 220V		MAX. 0.045A
VOLUME		MAX. 80dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		φ23 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY/FLASHING LIGHT			

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓞ	v	-
0.5~3			±0.2		
3~6	±0.05	±0.1	±0.3	±0.5	
6~30	±0.1	±0.2	±0.5	±1	
30~120	±0.15	±0.3	±0.8	±1.5	
120~400	±0.2	±0.5	±1.2	±2.5	
400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

SURFACE FINISH			-		1		-	
Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE			
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE			
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30			
TITLE			MODEL					
Q60LP OUTLINE DRAWING			Q60LP					
			DWG. NO.					
			Q60LP_OUT					
SCALE		SIZE	REV	SHEET				
N/S		A4	00	1/1				