



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	QA125HLS				
MATERIAL	LENS-PC				
	HOUSING-PC				
	-				
COLOR OF LENS	RED( ), AMBER( )				
FLASHES PER MIN.	60 ~ 80				
USE VOLT.	LED	CURRENT	DC12V ~ 24V	0.2W	MAX. 1.650A
PROTECTION GRADE	WATER & DUST PROOF IP66				
CABLE ENTRY	$\phi 10$ LEAD HOLE				
COLOR OF HOUSING	MAKER STANDARD				
ACTION	LED STROBE LAMP LIGHT				

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	(C)	v	
0.5-3	$\pm 0.05$	$\pm 0.1$	$\pm 0.2$	-	
3-6			$\pm 0.3$	$\pm 0.5$	
6-30	$\pm 0.1$	$\pm 0.2$	$\pm 0.5$	$\pm 1$	
30-120	$\pm 0.15$	$\pm 0.3$	$\pm 0.8$	$\pm 1.5$	
120-400	$\pm 0.2$	$\pm 0.5$	$\pm 1.2$	$\pm 2.5$	
400-1000	$\pm 0.3$	$\pm 0.8$	$\pm 2$	$\pm 4$	
FOR ANGULAR DIMENSIONS	0-10	$\pm 1^\circ$	$\pm 1^\circ 30'$	$\pm 3^\circ$	
	10-50	$\pm 0^\circ 30'$	$\pm 1^\circ$	$\pm 2^\circ$	
	50-120	$\pm 0^\circ 20'$	$\pm 0^\circ 30'$	$\pm 1^\circ$	
	120-400	$\pm 0^\circ 10'$	$\pm 0^\circ 13'$	$\pm 0^\circ 30'$	

SURFACE FINISH		-							
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE			
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE				
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.10.05				
TITLE				MODEL					
QA125HLS OUTLINE DRAWING				QA125HLS					
				DWG. NO.		QA125HLS_OUT			
SCALE	SIZE	REV	SHEET						
N/S	A4	00	1/1						