



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		QAD100BZ			
MATERIAL		HOUSING-ABS			
		LENS-PC			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES. PER MIN		60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	0.5W	MAX.0.550A
			DC24V		MAX.0.300A
			AC110V~220V		MAX.0.100A
VOLUME		MAX. 105dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓞ	v	-
0.5-3			±0.2		
3-6	±0.05	±0.1	±0.3	±0.5	
6-30	±0.1	±0.2	±0.5	±1	
30-120	±0.15	±0.3	±0.8	±1.5	
120-400	±0.2	±0.5	±1.2	±2.5	
400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°
	10-50	±0°30'		±1°	±2°
	50-120	±0°20'		±0°30'	±1°
	120-400	±0°10'		±0°13'	±0°30'

-	-	-	-	1	-
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
QAD100BZ OUTLINE DRAWING			QAD100BZ		
			DWG. NO.		
			QAD100BZ_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		