



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		QAD125BZ			
MATERIAL		HOUSING-ABS			
		LENS-PC			
COLOR OF LENS		RED( ), AMBER( ), GREEN( ), BLUE( )			
FLASHES. PER MIN		60 - 80			
USE VOLT.	LED	CURRNET	DC12V	0.5W	MAX.0.550A
			DC24V		MAX.0.300A
			AC110V~220V		MAX.0.100A
VOLUME		MAX. 105dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS		f	m	Ⓢ		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3-6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6-30	±0.1	±0.2	±0.5	±1	TITLE QAD125BZ OUTLINE DRAWING					
	30-120	±0.15	±0.3	±0.8	±1.5	MODEL QAD125BZ					
120-400	±0.2	±0.5	±1.2	±2.5	DWG. NO. QAD125BZ_OUT						
400-1000	±0.3	±0.8	±2	±4	SCALE N/S		SIZE A4	REV 00	SHEET 1/1		
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°						
	10-50	±0°30'		±1°	±2°						
	50-120	±0°20'		±0°30'	±1°						
	120-400	±0°10'		±0°13'	±0°30'						