



MARK	DATE	REVISION	REVISER	APP .BY

MODEL NO		QMCL80			
MATERIAL		HOUSING-ABS			
LENS-AS					
COLOR OF LENS		7 COLORS			
USE VOLT.	LED	CURRENT	DC12V	0.2W	MAX. 0.120A
			DC24V		MAX. 0.060A
VOLUME		MAX. 80dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP65			
CABLE ENTRY		$\phi 9$ LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-			1	-
FOR LINEAR DIMENSIONS	0.5-3	f	m	⊙	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	3-6	±0.05	±0.1	±0.2	±0.5	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6-30	±0.1	±0.2	±0.5	±1	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	30-120	±0.15	±0.3	±0.8	±1.5	TITLE			MODEL		
	120-400	±0.2	±0.5	±1.2	±2.5	QMCL100			QMCL80		
	400-1000	±0.3	±0.8	±2	±4	OUTLINE DRAWING			DWG. NO.		
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°				QMCL80_OUT		
	10-50	±0°30'		±1°	±2°				SCALE		
	50-120	±0°20'		±0°30'	±1°				SIZE		
	120-400	±0°10'		±0°13'	±0°30'				REV		
									SHEET		
									N/S		
									A4		
									00		
									1/1		