



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QMHL-150-MF			
MATERIAL		BODY-AL			
		LENS-CHEMICAL TEMPERED GLASS			
		COVER-AL			
		BRACKET-AL			
COLOR OF LENS					
CLEAR					
USE VOLT.	LED	CURRENT	CHIP LED	DC24V	MAX. 0.510A
				AC110V	MAX. 0.105A
				AC220V	MAX. 0.051A
PROTECTION GRADE		WATER & DUST PROOF IP67 / IP69K			
CABLE ENTRY		M12			

※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5-3	±0.05	±0.1	±0.2	-	
	3-6			±0.3	±0.5	
	6-30	±0.1	±0.2	±0.5	±1	
	30-120	±0.15	±0.3	±0.8	±1.5	
	120-400	±0.2	±0.5	±1.2	±2.5	
	400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°	
	10-50	±0°30'		±1°	±2°	
	50-120	±0°20'		±0°30'	±1°	
	120-400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME		MAT'L	1	
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	REFERENCE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE			MODEL			
QMHL-150-MF OUTLINE DRAWING			QMHL-150-MF			
			DWG. NO.			
			QMHL-150-MF_OUT			
SCALE		SIZE	REV	SHEET		
N/S		A4	00	1/1		