



4-φ45 FITTING HOLES

CABLE ENTRY M12

※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		QMHL-250-D			
MATERIAL		BODY-AL			
		LENS-CHEMICAL TEMPERED GLASS			
		COVER-AL			
		-			
COLOR OF LENS		CLEAR			
USE VOLT.	LED	CURRENT	CHIP LED	DC24V	MAX. 1.020A
				AC110V	MAX. 0.208A
				AC220V	MAX. 0.102A
PROTECTION GRADE		WATER & DUST PROOF IP67 / IP69K			
CABLE ENTRY		M12			

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓢ	v	
0.5-3	±0.05	±0.1	±0.2	-	
3-6			±0.3	±0.5	
6-30	±0.1	±0.2	±0.5	±1	
30-120	±0.15	±0.3	±0.8	±1.5	
120-400	±0.2	±0.5	±1.2	±2.5	
400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°	±1°30'	±3°	
	10-50	±0°30'	±1°	±2°	
	50-120	±0°20'	±0°30'	±1°	
	120-400	±0°10'	±0°13'	±0°30'	

SURFACE FINISH		-		1		-	
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE	
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE		
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30		
TITLE				MODEL			
QMHL-250-D OUTLINE DRAWING				QMHL-250-D			
				DWG. NO.			
				QMHL-250-D_OUT			
SCALE		SIZE	REV	SHEET			
N/S		A4	00	1/1			