



※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		QMHL-250-K			
MATERIAL		BODY-AL			
		LENS-CHEMICAL TEMPERED GLASS			
		COVER-AL			
		BRACKET-SUS430			
COLOR OF LENS		CLEAR			
USE VOLT.	LED	CURRENT	CHIP LED	DC24V	MAX. 1.020A
				AC110V	MAX. 0.208A
				AC220V	MAX. 0.102A
PROTECTION GRADE		WATER & DUST PROOF IP67 / IP69K			
CABLE ENTRY		M12			

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
	f	m	Ⓢ	v	Nr.		DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE	
	0.5-3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3-6			±0.3	±0.5							
	6-30	±0.1	±0.2	±0.5	±1		TITLE QMHL-250-K OUTLINE DRAWING		MODEL QMHL-250-K			
	30-120	±0.15	±0.3	±0.8	±1.5				DWG. NO. QMHL-250-K_OUT			
	120-400	±0.2	±0.5	±1.2	±2.5				SCALE N/S	SIZE A4	REV 00	SHEET 1/1
	400-1000	±0.3	±0.8	±2	±4							
FOR ANGULAR DIMENSION	0-10	±1°		±1°30'	±3°							
	10-50	±0°30'		±1°	±2°							
	50-120	±0°20'		±0°30'	±1°							
	120-400	±0°10'		±0°13'	±0°30'							