



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		QML-150-MF		
MATERIAL		BODY-AL		
		LENS-CHEMICAL TEMPERED GLASS		
		COVER-AL		
		BRACKET-AL		
COLOR OF LENS				
UNCLEAR				
USE VOLT.	LED	CURRENT	CHIP LED	MAX. 1.250A
				MAX. 0.215A
				MAX. 0.104A
PROTECTION GRADE		WATER & DUST PROOF IP67 / IP69K		
CABLE ENTRY		M12		

※ POWER CABLE : Dura & Flex-F VU(0.5sq X 2C) 450mm

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-			
	f	m	Ⓢ	v	Nr.		DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE			
	0.5-3	±0.05	±0.1	±0.2	-									
	3-6			±0.3	±0.5									
	6-30	±0.1	±0.2	±0.5	±1									
	30-120	±0.15	±0.3	±0.8	±1.5									
	120-400	±0.2	±0.5	±1.2	±2.5									
	400-1000	±0.3	±0.8	±2	±4									
FOR ANGULAR DIMENSIONS	0-10		±1°	±1°30'	±3°									
	10-50		±0°30'	±1°	±2°									
	50-120		±0°20'	±0°30'	±1°									
	120-400		±0°10'	±0°13'	±0°30'									
DSND BY S.H.KIM							CHKD BY J.H.PARK		APRV BY J.K.HAN		VIEW 3		DATE 2016.08.30	
TITLE QML-250-MF OUTLINE DRAWING							MODEL QML-250-MF							
							DWG. NO. QML-250-MF_OUT							
SCALE N/S			SIZE A4		REV 00		SHEET 1/1							