



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		S125DLR			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		REFLECTOR-HEAT RESISTING ABS			
REV. PER MIN.		120 ~ 140			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
USE VOLT.	LED	CURRENT	DC12V	1W	MAX. 0.483A
			DC24V		MAX. 0.327A
			AC110V		MAX. 0.120A
			AC220V		MAX. 0.060A
KIND OF SOUND		WS	5 Warning Sounds		
		WM	5 Melodie		
		WA	5 Alarms		
		WV	5 Customizable sounds		
VOLUME		MAX. 105dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP54			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED REVOLVING WARNING LIGHT			

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓢ	v	-
0.5-3			±0.2		
3-6	±0.05	±0.1	±0.3	±0.5	
6-30	±0.1	±0.2	±0.5	±1	
30-120	±0.15	±0.3	±0.8	±1.5	
120-400	±0.2	±0.5	±1.2	±2.5	
400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°
	10-50	±0°30'		±1°	±2°
	50-120	±0°20'		±0°30'	±1°
	120-400	±0°10'		±0°13'	±0°30'

SURFACE FINISH			-			1			-		
Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE						
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE						
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30						
TITLE			MODEL								
S125DLR OUTLINE DRAWING			S125DLR								
			DWG. NO.								
			S125DLR_OUT								
SCALE		SIZE	REV	SHEET							
N/S		A4	00	1/1							