



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		S150RS			
MATERIAL		HOUSING-SUS			
		LENS-PC			
		REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS		RED( ), AMBER( ), GREEN( ), BLUE( )			
FLASHES PER MIN.		60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 1.001A
			DC24V		MAX. 0.616A
			AC110V		MAX. 0.133A
			AC220V		MAX. 0.106A
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	(C)	
		0.5~3	±0.05	±0.1	±0.2
3~6				±0.3	±0.5
6~30		±0.1	±0.2	±0.5	±1
30~120		±0.15	±0.3	±0.8	±1.5
120~400		±0.2	±0.5	±1.2	±2.5
	400~1000	±0.3	±0.8	±2	±4
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°
	10~50	±0°30'		±1°	±2°
	50~120	±0°20'		±0°30'	±1°
	120~400	±0°10'		±0°13'	±0°30'

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S150RS OUTLINE DRAWING			S150RS		
			DWG. NO.		
			S150RS_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		