



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO	S150R				
MATERIAL	HOUSING-SUS				
	LENS-PC				
	REFLECTOR-PC				
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()				
REV. PER MIN.	120 ~ 140				
USE VOLT.	BLUB	CURRENT	DC12V	15W	MAX. 1.155A
			DC24V		MAX. 0.766A
			AC110V		MAX. 0.204A
			AC220V		MAX. 0.102A
PROTECTION GRADE	WATER & DUST PROOF IP44				
CABLE ENTRY	φ10 LEAD HOLE				
COLOR OF HOUSING	MAKER STANDARD				
ACTION	BULB REVOLVING WARNING LIGHT				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	⊙	v	
		0.5-3			±0.2	-
	3-6	±0.05	±0.1	±0.3	±0.5	
	6-30	±0.1	±0.2	±0.5	±1	
	30-120	±0.15	±0.3	±0.8	±1.5	
	120-400	±0.2	±0.5	±1.2	±2.5	
	400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°	
	10-50	±0°30'		±1°	±2°	
	50-120	±0°20'		±0°30'	±1°	
	120-400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	1	-
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S150R OUTLINE DRAWING			S150R		
			DWG. NO.	S150R_OUT	
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		