



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		S60LR		
MATERIAL		HOUSING-ABS		
		LENS-AS		
		REFLECTOR-HEAT RESISTING ABS		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN		120 ~ 140		
USE VOLT.	POWER LED	CURRENT	DC12V	MAX. 0.183A
			DC24V	MAX. 0.127A
			AC110V	MAX. 0.040A
			AC220V	MAX. 0.020A
PROTECTION GRADE		WATER & DUST PROOF IP44		
CABLE ENTRY		φ8 LEAD HOLE		
COLOR OF HOUSING		MAKER STANDARD		
ACTION		POWER LED REVOLVING WARNING LIGHT		

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S60LR OUTLINE DRAWING			S60LR		
			DWG. NO.		
			S60LR_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		