



MARK	DATE	REVISION	REVISER	APP.BY
△1				
△2				
△3				

MODEL NO		S60L			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.		60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.118A
			DC24V		MAX. 0.083A
			AC110V		MAX. 0.026A
			AC220V		MAX. 0.013A
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		φ8 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY/FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					
FOR LINEAR DIMENSIONS		f	m	⊙	v
		0.5-3			±0.2
3-6	±0.05	±0.1	±0.3	±0.5	
6-30	±0.1	±0.2	±0.5	±1	
30-120	±0.15	±0.3	±0.8	±1.5	
120-400	±0.2	±0.5	±1.2	±2.5	
400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS		±1°		±1°30'	±3°
		0-10			
		10-50	±0°30'	±1°	±2°
		50-120	±0°20'	±0°30'	±1°
120-400	±0°10'	±0°13'	±0°30'		

SURFACE FINISH			-		1	-
Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE	
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE			MODEL			
S60L OUTLINE DRAWING			S60L			
			DWG. NO.			
			S60L_OUT			
SCALE	SIZE	REV	SHEET			
N/S	A4	00	1/1			