



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		S80AS			
MATERIAL		HOUSING-ABS			
		LENS-AS			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHES PER MIN.		60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	4W	MAX. 0.433A
			DC24V		MAX. 0.216A
			AC110V		MAX. 0.076A
			AC220V		MAX. 0.061A
VOLUME		MAX. 90dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		φ8 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	Ⓞ	v	
		0.5~3			±0.2	-
	3~6	±0.05	±0.1	±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

-	-	-	-	1	-	
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE			MODEL			
S80AS OUTLINE DRAWING			S80AS			
			DWG. NO.			
			S80AS_OUT			
SCALE	SIZE	REV	SHEET			
N/S	A4	00	1/1			