



MARK	DATE	REVISION	REVISER	APP .BY
$\triangle 1$				
$\triangle 2$				
$\triangle 3$				

MODEL NO		S80AU			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.		120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	5W	MAX. 0.484A
			DC24V		MAX. 0.310A
			AC110V		MAX. 0.080A
			AC220V		MAX. 0.040A
VOLUME		MAX. 90dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		$\phi 8$ LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		1		-		
FOR LINEAR DIMENSIONS	f		m		Ⓞ		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5~3					± 0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3~6	± 0.05		± 0.1		± 0.3	± 0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6~30	± 0.1		± 0.2		± 0.5	± 1	TITLE		MODEL			
	30~120	± 0.15		± 0.3		± 0.8	± 1.5	S80AU		S80AU			
	120~400	± 0.2		± 0.5		± 1.2	± 2.5	OUTLINE DRAWING		S80AU_OUT			
400~1000	± 0.3		± 0.8		± 2	± 4			DWG. NO.				
FOR ANGULAR DIMENSIONS	0~10		$\pm 1^\circ$		$\pm 1^\circ 30'$	$\pm 3^\circ$	SCALE		SIZE	REV	SHEET		
	10~50		$\pm 0^\circ 30'$		$\pm 1^\circ$	$\pm 2^\circ$	N/S		A4	00	1/1		
	50~120		$\pm 0^\circ 20'$		$\pm 0^\circ 30'$	$\pm 1^\circ$							
	120~400		$\pm 0^\circ 10'$		$\pm 0^\circ 13'$	$\pm 0^\circ 30'$							