



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		S80RK			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.		120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	5W	MAX. 0.484A
			DC24V		MAX. 0.310A
			AC110V		MAX. 0.080A
			AC220V		MAX. 0.040A
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		φ13 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS	f	m	⊙	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5-3			±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3-6	±0.05	±0.1	±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6-30	±0.1	±0.2	±0.5	±1	TITLE		S80RK		MODEL		
	30-120	±0.15	±0.3	±0.8	±1.5	OUTLINE DRAWING		S80RK				
	120-400	±0.2	±0.5	±1.2	±2.5			DWG. NO.				
400-1000	±0.3	±0.8	±2	±4			S80RK_OUT					
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°	SCALE	SIZE	REV	SHEET			
	10-50	±0°30'		±1°	±2°	N/S	A4	00	1/1			
	50-120	±0°20'		±0°30'	±1°							
	120-400	±0°10'		±0°13'	±0°30'							