



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO		S80R			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.		120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	5W	MAX. 0.484A
			DC24V		MAX. 0.310A
			AC110V		MAX. 0.080A
			AC220V		MAX. 0.040A
VOLUME		MAX. 90dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		Ø10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS	f		m		⊙		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5-3				±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3-6		±0.05	±0.1	±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6-30		±0.1	±0.2	±0.5	±1	TITLE					
	30-120		±0.15	±0.3	±0.8	±1.5	S80R					
	120-400		±0.2	±0.5	±1.2	±2.5	OUTLINE DRAWING					
400-1000		±0.3	±0.8	±2	±4	MODEL						
0-10		±1°		±1°30'	±3°	S80R						
10-50		±0°30'		±1°	±2°	DWG. NO.						
50-120		±0°20'		±0°30'	±1°	S80R_OUT						
120-400		±0°10'		±0°13'	±0°30'	SCALE	SIZE	REV	SHEET			
						N/S	A4	00	1/1			