



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		S80S			
MATERIAL		HOUSING-ABS			
		LENS-AS			
COLOR OF LENS		RED( ), AMBER( ), GREEN( ), BLUE( )			
FLASHES. PER MIN.		60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	4W	MAX. 0.433A
			DC24V		MAX. 0.216A
			AC110V		MAX. 0.076A
			AC220V		MAX. 0.061A
PROTECTION GRADE		WATER & DUST PROOF IP54			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS	f	m	⊙	v			Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5-3			±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3-6	±0.05	±0.1	±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6-30	±0.1	±0.2	±0.5	±1	TITLE		S80S		MODEL		
	30-120	±0.15	±0.3	±0.8	±1.5	OUTLINE DRAWING		S80S_OUT		DWG. NO.		
	120-400	±0.2	±0.5	±1.2	±2.5			SCALE		SIZE	REV	SHEET
400-1000	±0.3	±0.8	±2	±4			N/S		A4	00	1/1	
FOR ANGULAR DIMENSIONS	±1°		±1°30'	±3°								
	0-10											
	10-50	±0°30'	±1°	±2°								
	50-120	±0°20'	±0°30'	±1°								
120-400	±0°10'	±0°13'	±0°30'									