



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		S80UK			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		REFLECTOR-HEAT RESISTING ABS			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.		120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	5W	MAX. 0.484A
			DC24V		MAX. 0.310A
			AC110V		MAX. 0.080A
			AC220V		MAX. 0.040A
PROTECTION GRADE		WATER & DUST PROOF IP44			
CABLE ENTRY		$\phi 13$ LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH
FOR LINEAR DIMENSIONS		f	m	Ⓞ	v	
		0.5~3			±0.2	-
3~6		±0.05	±0.1	±0.3	±0.5	
6~30		±0.1	±0.2	±0.5	±1	
30~120		±0.15	±0.3	±0.8	±1.5	
120~400		±0.2	±0.5	±1.2	±2.5	
400~1000		±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

-	-	-	-	1	-
Nr.	DWG. NO.	TITLE/ NAME		MAT'L	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
S80UK OUTLINE DRAWING			S80UK		
			DWG. NO.		
			S80UK_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		