



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO	SC3			
MATERIAL	HOUSING-ABS			
	LENS-AS			
	REFLECTOR-HEAT RESISTING ABS			
	PROTECTION CAGE-SUS316L			
	BRACKET-STEEL			
	HORN HOUSING-ABS			
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN	120 ~ 140			
USE VOLT.	BULB	CURRENT	DC12V	MAX. 3.755A
			DC24V	MAX. 1.788A
			AC110V	MAX. 0.430A
			AC220V	MAX. 0.215A
VOLUME	MAX. 118dB			
PROTECTION GRADE	WATER & DUST PROOF IP44			
CABLE ENTRY	1/2" PF			
COLOR OF HOUSING	MAKER STANDARD			
ACTION	BULB REVOLVING WARNING LIGHT			

※ *(371) represents size without protection cage.

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5-3	±0.05	±0.1	±0.2	-	
	3-6			±0.3	±0.5	
	6-30	±0.1	±0.2	±0.5	±1	
	30-120	±0.15	±0.3	±0.8	±1.5	
	120-400	±0.2	±0.5	±1.2	±2.5	
400-1000	±0.3	±0.8	±2	±4		
FOR ANGULAR DIMENSIONS	0-10		±1°	±1°30'	±3°	
	10-50		±0°30'	±1°	±2°	
	50-120		±0°20'	±0°30'	±1°	
	120-400		±0°10'	±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
SC3 OUTLINE DRAWING			SC3		
			DWG. NO.	SC3_OUT	
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		