



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO	SCDFL			
MATERIAL	HOUSING-PC+GF			
	LENS-PC			
	REFLECTOR-HEAT RESISTING ABS			
	PROTECTION CAGE-SUS316L			
COLOR OF LENS	RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.	60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	MAX. 2.511A
			DC24V	MAX. 1.222A
			AC110V	MAX. 0.286A
			AC220V	MAX. 0.143A
PROTECTION GRADE	WATER & DUST PROOF IP66			
CABLE ENTRY	1/2"PF			
COLOR OF HOUSING	MAKER STANDARD			
ACTION	LED STEADY/FLASHING LIGHT			

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5-3	±0.05	±0.1	±0.2	-	
	3-6			±0.3	±0.5	
	6-30	±0.1	±0.2	±0.5	±1	
	30-120	±0.15	±0.3	±0.8	±1.5	
	120-400	±0.2	±0.5	±1.2	±2.5	
	400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°	
	10-50	±0°30'		±1°	±2°	
	50-120	±0°20'		±0°30'	±1°	
	120-400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
SCDFL OUTLINE DRAWING			SCDFL		
			DWG. NO.	SCDFL_OUT	
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		