



※ *(410) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		SD		
MATERIAL		HOUSING-AL		
		LENS-PC		
		REFLECTOR-HEAT RESISTING ABS		
		PROTECTION CAGE-SUS316L		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN.		120 ~ 140		
USE VOLT.	BULB	CURRENT	15W	MAX. 3.755A
				MAX. 1.788A
				MAX. 0.422A
				MAX. 0.211A
PROTECTION GRADE		WATER & DUST PROOF IP66		
CABLE ENTRY		1/2" PF		
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2		
ACTION		BULB REVOLVING WARNING LIGHT		

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5-3	±0.05	±0.1	±0.2	-	
	3-6			±0.3	±0.5	
	6-30	±0.1	±0.2	±0.5	±1	
	30-120	±0.15	±0.3	±0.8	±1.5	
	120-400	±0.2	±0.5	±1.2	±2.5	
	400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10		±1°	±1°30'	±3°	
	10-50		±0°30'	±1°	±2°	
	50-120		±0°20'	±0°30'	±1°	
	120-400		±0°10'	±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
SD OUTLINE DRAWING			SD		
			DWG. NO.		
			SD_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		