



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		SED		
MATERIAL		HOUSING-AL		
		LENS-PC		
		REFLECTOR-HEAT RESISTING ABS		
		PROTECTION CAGE-SUS316L		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
REV. PER MIN.		120 ~ 140		
USE VOLT.	BULB	CURRENT	15W	MAX. 3.755A
				MAX. 1.788A
				MAX. 0.422A
				MAX. 0.211A
PROTECTION GRADE		WATER & DUST PROOF IP66		
CABLE ENTRY		1/2" PF		
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2		
ACTION		BULB REVOLVING WARNING LIGHT		

※ *(380) represents size without protection cage.

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS		f	m	(C)		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY			VIEW	DATE
	3-6			±0.3	±0.5	S.H.KIM	J.H.PARK	J.K.HAN	3	2016.08.30	
	6-30	±0.1	±0.2	±0.5	±1	TITLE SED OUTLINE DRAWING					
	30-120	±0.15	±0.3	±0.8	±1.5	MODEL SED					
	120-400	±0.2	±0.5	±1.2	±2.5	DWG. NO. SED_OUT					
400-1000	±0.3	±0.8	±2	±4	SCALE N/S		SIZE A4	REV 00	SHEET 1/1		
FOR ANGULAR DIMENSIONS	0-10	±1°	±1°30'	±3°							
	10-50	±0°30'	±1°	±2°							
	50-120	±0°20'	±0°30'	±1°							
	120-400	±0°10'	±0°13'	±0°30'							