



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SESAS		
MATERIAL		HOUSING-AL		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
FLASHING PER MIN.		60 - 80		
USE VOLT.	XENON	CURRENT	DC12V	MAX. 2.933A
			DC24V	MAX. 1.411A
			AC110V	MAX. 0.360A
			AC220V	MAX. 0.220A
VOLUME		MAX. 118dB		
PROTECTION GRADE		WATER & DUST PROOF IP66		
CABLE ENTRY		1/2" NPT		
COLOR OF HOUSING		MUNSELL NO.7.5BG 7/2		
ACTION		XENON LAMP STROBE LIGHT		

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
0.5-3	±0.05	±0.1	±0.2	-		
3-6			±0.3	±0.5		
6-30	±0.1	±0.2	±0.5	±1		
30-120	±0.15	±0.3	±0.8	±1.5		
120-400	±0.2	±0.5	±1.2	±2.5		
400-1000	±0.3	±0.8	±2	±4		
FOR ANGULAR DIMENSIONS	0-10	±1°	±1°30'	±3°		
	10-50	±0°30'	±1°	±2°		
	50-120	±0°20'	±0°30'	±1°		
	120-400	±0°10'	±0°13'	±0°30'		

Nr.	DWG. NO.	TITLE/ NAME		MAT'L	1	
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	REFERENCE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE				MODEL		
SESAS OUTLINE DRAWING				SESAS		
				DWG. NO.		
				SESAS_OUT		
SCALE		SIZE	REV	SHEET		
N/S		A4	00	1/1		