



※ *(167) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SH1S		
MATERIAL		HOUSING-AL		
		LENS-PC		
		PROTECTION CAGE-SUS316L		
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()		
FLASHING PER MIN.		60 - 80		
USE VOLT.	XENON	CURRENT	DC12V	MAX. 1.001A
			DC24V	MAX. 0.616A
			AC110V	MAX. 0.133A
			AC220V	MAX. 0.106A
		6W		
PROTECTION GRADE		WATER & DUST PROOF IP66		
CABLE ENTRY		1/2" PF		
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2		
ACTION		XENON LAMP STROBE LIGHT		

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS		f	m	Ⓢ		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	TITLE/ NAME	MAT'L	VIEW	DATE
	3-6			±0.3	±0.5	S.H.KIM	J.H.PARK	SH1S	J.K.HAN	3	2016.08.30
	6-30	±0.1	±0.2	±0.5	±1			OUTLINE DRAWING	MODEL	SH1S	
	30-120	±0.15	±0.3	±0.8	±1.5				DWG. NO.	SH1S_OUT	
	120-400	±0.2	±0.5	±1.2	±2.5				SCALE	SIZE	REV
400-1000	±0.3	±0.8	±2	±4				N/S	A4	00	1/1
FOR ANGULAR DIMENSIONS											
	0-10		±1°	±1°30'	±3°						
	10-50		±0°30'	±1°	±2°						
	50-120		±0°20'	±0°30'	±1°						
120-400		±0°10'	±0°13'	±0°30'							