



※ *(167) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		SH1			
MATERIAL		HOUSING-AL			
		LENS-PC			
		REFLECTOR-PC			
		PROTECTION CAGE-SUS316L			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
REV. PER MIN.		120~140			
USE VOLT.	BULB	CURRENT	DC12V	15W	MAX. 1.544A
			DC24V		MAX. 0.766A
			AC110V		MAX. 0.204A
			AC220V		MAX. 0.102A
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		1/2" PF			
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2			
ACTION		BULB REVOLVING WARNING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS		f	m	Ⓢ		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	TITLE/ NAME	APRV BY	VIEW	DATE
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK	SH1	J.K.HAN	3	2016.08.30
	6~30	±0.1	±0.2	±0.5	±1			SH1			
	30~120	±0.15	±0.3	±0.8	±1.5			SH1			
120~400	±0.2	±0.5	±1.2	±2.5			SH1				
400~1000	±0.3	±0.8	±2	±4			SH1				
FOR ANGULAR DIMENSIONS						TITLE		MODEL			
	0~10	±1°	±1°	±1°30'	±3°	SH1		SH1			
	10~50	±0°30'	±1°	±2°		SH1		SH1			
	50~120	±0°20'	±0°30'	±1°		SH1		SH1			
120~400	±0°10'	±0°13'	±0°30'		SH1		SH1				
						DWG. NO.		SH1_OUT			
						SCALE	SIZE	REV	SHEET		
						N/S	A4	00	1/1		

A4(297X210)