



※ *(198) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		SH2S			
MATERIAL		HOUSING-AL			
		LENS-PC			
		PROTECTION CAGE-SUS316L			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.		60 ~ 80			
USE VOLT.	LED	CURRENT	DC12V	6W	MAX. 1.001A
			DC24V		MAX. 0.616A
			AC110V		MAX. 0.133A
			AC220V		MAX. 0.106A
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		1/2" PF			
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2			
ACTION		XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
		0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
		3-6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
		6-30	±0.1	±0.2	±0.5	±1	TITLE SH2S OUTLINE DRAWING					
		30-120	±0.15	±0.3	±0.8	±1.5	MODEL SH2S					
		120-400	±0.2	±0.5	±1.2	±2.5	DWG. NO. SH2S_OUT					
	400-1000	±0.3	±0.8	±2	±4	SCALE N/S		SIZE A4	REV 00	SHEET 1/1		
FOR ANGULAR DIMENSIONS				Ⓢ	v							
		0-10	±1°	±1°30'	±3°							
		10-50	±0°30'	±1°	±2°							
		50-120	±0°20'	±0°30'	±1°							
	120-400	±0°10'	±0°13'	±0°30'								