



※ *(198)치수는 SH2TLR/SH2TL/SH2TS/SH2T 모델의 보호망 미장착 시 치수입니다.

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SH2TS			
MATERIAL		HOUSING-AL LENS-PC PROTECTION GAGE-SUS316L			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.		60~80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 1.001A
			DC24V		MAX. 0.616A
			AC110V		MAX. 0.133A
			AC220V		MAX. 0.106A
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		1/2" PF			
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2			
ACTION		XENON LAMP STROBE LIGHT			

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	
	10~50	±0°30'		±1°	±2°	
	50~120	±0°20'		±0°30'	±1°	
	120~400	±0°10'		±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
TITLE			MODEL		
SH2TS OUTLINE DRAWING			SH2TS		
			DWG. NO.		
			SH2TS_OUT		
SCALE	SIZE	REV	SHEET		
N/S	A4	00	1/1		