



MARK	DATE	REVISION	REVISER	APP .BY
△				
△				
△				

MODEL NO		SKTLM			
MATERIAL		HOUSING-PC			
		LENS-PC			
		-			
COLOR OF LENS		RED( ), AMBER( )			
FLASHES. PER MIN		60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	3W	MAX.1.000V
			DC24V		MAX.0.555V
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		ø9 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-			1	-	
FOR LINEAR DIMENSIONS	0.5~3	f	m	⊙	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	3~6	±0.05	±0.1	±0.2	±0.3	±0.5	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	6~30	±0.1	±0.2	±0.5	±1		S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	30~120	±0.15	±0.3	±0.8	±1.5		TITLE			MODEL		
	120~400	±0.2	±0.5	±1.2	±2.5		SKTLM			SKTLM		
	400~1000	±0.3	±0.8	±2	±4		OUTLINE DRAWING			SKTLM_OUT		
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	DWG. NO.			SKTLM_OUT			
	10~50	±0°30'		±1°	±2°	SCALE		SIZE	REV	SHEET		
	50~120	±0°20'		±0°30'	±1°	N/S		A4	00	1/1		
	120~400	±0°10'		±0°13'	±0°30'							