



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SKTL			
MATERIAL		HOUSING-PC			
		LENS-PC			
		-			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE(), WHITE()			
FLASHES. PER MIN		60 ~ 80			
USE VOLT.	LED	CURRNET	DC12V	3W	MAX.1.000V
			DC24V		MAX.0.555V
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		Ø9 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		LED STEADY / FLASHING LIGHT			

	ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH
	f	m	Ⓢ	v		
FOR LINEAR DIMENSIONS	0.5~3	±0.05	±0.1	±0.2	-	
	3~6			±0.3	±0.5	
	6~30	±0.1	±0.2	±0.5	±1	
	30~120	±0.15	±0.3	±0.8	±1.5	
	120~400	±0.2	±0.5	±1.2	±2.5	
	400~1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0~10		±1°	±1°30'	±3°	
	10~50		±0°30'	±1°	±2°	
	50~120		±0°20'	±0°30'	±1°	
	120~400		±0°10'	±0°13'	±0°30'	

Nr.	DWG. NO.	TITLE/ NAME		MAT'L	QTY	REFERENCE
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
TITLE			SKTL	MODEL		
			OUTLINE DRAWING	SKTL		
				DWG. NO.		
				SKTL_OUT		
SCALE	SIZE	REV	SHEET			
N/S	A4	00	1/1			