


MARK	DATE	REVISION	REVISER	APP.BY
1				
2				
3				

MODEL NO		SM200		
MATERIAL		HOUSING-STEEL / AL		
USE VOLT.	CURRENT	DC24V	MAX. 7.820A	
		AC110V	MAX. 2.105A	
		AC220V	MAX. 1.005A	
VOLUME		MAX. 120dB		
PROTECTION GRADE		WATER & DUST PROOF IP44		
CABLE ENTRY		ø9 LEAD HOLE		
COLOR		RED		
RATING		10 MIN.		

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	⊕	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE	
	3~6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	6~30	±0.1	±0.2	±0.5	±1	TITLE			MODEL			
	30~120	±0.15	±0.3	±0.8	±1.5	SM200			SM200			
	120~400	±0.2	±0.5	±1.2	±2.5	OUTLINE DRAWING						
FOR ANGULAR DIMENSIONS	400~1000	±0.3	±0.8	±2	±4				DWG. NO.			
	0~10	±1°		±1°30'	±3°				SM200_OUT			
	10~50	±0°30'		±1°	±2°							
	50~120	±0°20'		±0°30'	±1°				SCALE			
	120~400	±0°10'		±0°13'	±0°30'				N/S			
								SIZE	REV	SHEET		
								A4	00	1/1		