



※ *(462) represents size without protection cage.

MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SMDS			
MATERIAL		HOUSING-AL			
		LENS-PC			
		PROTECTION CAGE-SUS316L			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.		60 ~ 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 2.822A
			DC24V		MAX. 1.444A
			AC110V		MAX. 0.377A
			AC220V		MAX. 0.228A
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		1/2" PF			
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2			
ACTION		XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH						
FOR LINEAR DIMENSIONS		f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY						
	3-6			±0.3	±0.5	CHKD BY				VIEW	DATE	
	6-30	±0.1	±0.2	±0.5	±1	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30	
	30-120	±0.15	±0.3	±0.8	±1.5	TITLE			MODEL			
	120-400	±0.2	±0.5	±1.2	±2.5	SMDS OUTLINE DRAWING			SMDS			
400-1000	±0.3	±0.8	±2	±4				DWG. NO.				
FOR ANGULAR DIMENSION	0-10	±1°		±1°30'	±3°				SMDS_OUT			
	10-50	±0°30'		±1°	±2°				SCALE	SIZE	REV	SHEET
	50-120	±0°20'		±0°30'	±1°				N/S	A4	00	1/1
	120-400	±0°10'		±0°13'	±0°30'							

A4(297X210)