



MARK	DATE	REVISION	REVISER	APP. BY
①				
②				
③				

MODEL NO		SNES-S			
MATERIAL		HOUSING-AL			
		LENS-PC			
		PROTECTION CAGE-SUS316L			
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE()			
FLASHING PER MIN.		60 - 80			
USE VOLT.	XENON	CURRENT	DC12V	6W	MAX. 0.655A
			DC24V		MAX. 0.500A
			AC110V		MAX. 0.104A
			AC220V		MAX. 0.066A
KIND OF SOUND		Buzzer	Warning Sounds		
			7 Sounds		
VOLUME		MAX. 105dB			
PROTECTION GRADE		WATER & DUST PROOF IP66			
CABLE ENTRY		1/2" NPT			
COLOR OF HOUSING		MUNSELL NO 7.5BG 7/2			
ACTION		XENON LAMP STROBE LIGHT			

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS		f	m	Ⓢ		v	Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	TITLE/ NAME	APRV BY	VIEW	DATE
	3-6			±0.3	±0.5	S.H.KIM	J.H.PARK	SNES-S	J.K.HAN	3	2016.08.30
	6-30	±0.1	±0.2	±0.5	±1			OUTLINE DRAWING	MODEL		
	30-120	±0.15	±0.3	±0.8	±1.5				SNES-S		
	120-400	±0.2	±0.5	±1.2	±2.5				SNES-S_OUT		
400-1000	±0.3	±0.8	±2	±4				SCALE	SIZE	REV	SHEET
FOR ANGULAR DIMENSIONS	0-10	±1°	±1°30'	±3°				N/S	A4	00	1/1
	10-50	±0°30'	±1°	±2°							
	50-120	±0°20'	±0°30'	±1°							
	120-400	±0°10'	±0°13'	±0°30'							