



MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO		SNESLR		
MATERIAL		HOUSING-AL		
		LENS-TMPERED GLASS		
		PROTECTION CAGE-ST316L		
		REFLECTOR-PC		
COLOR OF LENS		RED( ), AMBER( ), GREEN( ), BLUE( )		
PER. PER MIN.		120 ~ 140		
USE VOLT.	LED	CURRENT	DC12V	MAX. 0.485A
			DC24V	MAX. 0.411A
			AC110V	MAX. 0.111A
			AC220V	MAX. 0.055A
KIND OF SOUND		Buzzer	Warning Sounds 7 Sounds	
VOLUME		MAX. 105dB		
PROTECTION GRADE		WATER & DUST PROOF IP66		
CABLE ENTRY		1/2" NPT		
COLOR OF HOUSING		MUNSELL NO. 7.5BG 7/2		
ACTION		LED REVOLVING WARNING LIGHT		

ISO2768-1 : CLASS OF TOLERANCE					SURFACE FINISH	-		1		-	
FOR LINEAR DIMENSIONS	f	m	Ⓢ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3-6			±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6-30	±0.1	±0.2	±0.5	±1	TITLE SNESLR OUTLINE DRAWING					
	30-120	±0.15	±0.3	±0.8	±1.5	MODEL SNESLR					
	120-400	±0.2	±0.5	±1.2	±2.5	DWG. NO. SNESLR_OUT					
400-1000	±0.3	±0.8	±2	±4	SCALE N/S		SIZE A4	REV 00	SHEET 1/1		
FOR ANGULAR DIMENSIONS	0-10	±1°	±1°30'	±3°							
	10-50	±0°30'	±1°	±2°							
	50-120	±0°20'	±0°30'	±1°							
	120-400	±0°10'	±0°13'	±0°30'							