


MARK	DATE	REVISION	REVISER	APP .BY
①				
②				
③				

MODEL NO			SSL100W			
MATERIAL			HOUSING-AL			
			LENS-PC			
COLOR OF LENS			RED(    ), AMBER(    ), GREEN(    ), BLUE(    )			
USE VOLT.	LED	CURRENT	DC12V	0.08W	MAX. 0.280A	
			DC24V		MAX. 0.151A	
			AC110V		MAX. 0.040A	
			AC220V		MAX. 0.040A	
PROTECTION GRADE			WATER & DUST PROOF IP68			
CONNECTOR			M12-5PIN			
COLOR OF HOUSING			MAKER STANDARD			
ACTION			LED STEADY			

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH	-	-	-	-	1	-
FOR LINEAR DIMENSIONS		f	m	Ⓒ	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QT'Y	REFERENCE
	0.5~3	±0.05	±0.1	±0.2	-		DSND BY S.H.KIM	CHKD BY J.H.PARK	CHKD BY 	APRV BY J.K.HAN	VIEW 3	DATE 2016.08.30
	3~6			±0.3	±0.5							
	6~30	±0.1	±0.2	±0.5	±1							
	30~120	±0.15	±0.3	±0.8	±1.5							
	120~400	±0.2	±0.5	±1.2	±2.5							
400~1000	±0.3	±0.8	±2	±4								
FOR ANGULAR DIMENSIONS	0~10	±1°		±1°30'	±3°	TITLE SSL100W OUTLINE DRAWING			MODEL SSL100W			
	10~50	±0°30'		±1°	±2°				DWG. NO. SSL100W_OUT			
	50~120	±0°20'		±0°30'	±1°				SCALE N/S			
	120~400	±0°10'		±0°13'	±0°30'				SIZE A4			
									REV 00		SHEET 1/1	

A4(297X210)