



MARK	DATE	REVISION	REVISER	APP.BY
△				
△				
△				

MODEL NO		STND125R			
MATERIAL		HOUSING-ABS			
		LENS-AS			
		-			
COLOR OF LENS		RED( ), AMBER( ), GREEN( ), BLUE( )			
FLASHES. PER MIN		120 ~ 140			
USE VOLT.	BULB	CURRNET	DC12V	10W	MAX. 1.420A
			DC24V		MAX. 0.820A
			AC110V		MAX. 0.230A
			AC220V		MAX. 0.130A
VOLUME		MAX. 105dB at 1m			
PROTECTION GRADE		WATER & DUST PROOF IP54			
CABLE ENTRY		φ10 LEAD HOLE			
COLOR OF HOUSING		MAKER STANDARD			
ACTION		BULB REVOLVING WARNING LIGHT			

FOR LINEAR DIMENSIONS	ISO2768-1 : CLASS OF TOLERANCE				
	f	m	Ⓞ	v	-
0.5-3			±0.2		
3-6	±0.05	±0.1	±0.3	±0.5	
6-30	±0.1	±0.2	±0.5	±1	
30-120	±0.15	±0.3	±0.8	±1.5	
120-400	±0.2	±0.5	±1.2	±2.5	
400-1000	±0.3	±0.8	±2	±4	
FOR ANGULAR DIMENSIONS	0-10	±1°		±1°30'	±3°
	10-50	±0°30'		±1°	±2°
	50-120	±0°20'		±0°30'	±1°
	120-400	±0°10'		±0°13'	±0°30'

SURFACE FINISH			-			1			-		
Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY	REFERENCE						
DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE						
S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30						
TITLE			MODEL								
STND125R OUTLINE DRAWING			STND125R								
			DWG. NO.								
			STND125R_OUT								
SCALE	SIZE	REV	SHEET								
N/S	A4	00	1/1								