



MARK	DATE	REVISION	REVISER	APP.BY
①				
②				
③				

MODEL NO		QT50L-BZ				
MATERIAL		HOUSING-PC LENS-PC COVER-PC				
COLOR OF LENS		RED(), AMBER(), GREEN(), BLUE(), WHITE()				
KIND OF FUNCTION		USE VOLT.	STEADY	FLASHES	STROBE	REVOLVING
LED MODULE	USE VOLT.	LAYER 1 CURRNET (MAX.)	DC12V	0.080A	0.080A	0.100A 0.050A
			DC24V	0.040A	0.040A	0.120A 0.060A
			AC110V	0.018A	0.018A	- -
BUZZER MODULE	USE VOLT.	CURRNET (MAX.)	DC12V	0.015A		
			DC24V	0.028A		
			AC110V	0.021A		
			AC220V	0.038A		
PROTECTION GRADE		WATER & DUST PROOF IP65				
CABLE ENTRY		ø8 LEAD HOLE				
COLOR OF HOUSING		MAKER STANDARD				
ACTION		LED SIGNAL TOWER LAMP				

ISO2768-1 : CLASS OF TOLERANCE						SURFACE FINISH					
FOR LINEAR DIMENSIONS		f	m	⊙	v		Nr.	DWG. NO.	TITLE/ NAME	MAT'L	QTY
	0.5-3	±0.05	±0.1	±0.2	-	DSND BY	CHKD BY	CHKD BY	APRV BY	VIEW	DATE
	3-6	±0.05	±0.1	±0.3	±0.5	S.H.KIM	J.H.PARK		J.K.HAN	3	2016.08.30
	6-30	±0.1	±0.2	±0.5	±1	TITLE QT50L-BZ OUTLINE DRAWING					
	30-120	±0.15	±0.3	±0.8	±1.5	MODEL QT50L-BZ					
	120-400	±0.2	±0.5	±1.2	±2.5	DWG. NO. QT50L-BZ_OUT					
400-1000	±0.3	±0.8	±2	±4	SCALE N/S		SIZE A4	REV 00	SHEET 1/1		
FOR ANGULAR DIMENSIONS											
	0-10	±1°		±1°30'	±3°						
	10-50	±0°30'		±1°	±2°						
	50-120	±0°20'		±0°30'	±1°						
120-400	±0°10'		±0°13'	±0°30'							